

Items 7 and 8

Planning application: 20/00449/FULL

Listed building consent application: 20/00448/LBC

Former Tealing Parish Church, Kirkton of Tealing



Aerial


United Kingdom · Scotland · Angus



Feedback

50 feet 10 m

Image courtesy of Ordnance Survey



142.0m

Track

+

Hearse shed to be used as garage with no construction changes.

Kirkside

4 No GRAF Infiltration tunnels to provide suitable infiltration according to "Drainage Field Calculation using GRAF infiltration tunnels - Church Conversation" calculation document.

New GRAF 5 person waste water treatment system
See Griffen Design dwg: 214208-01-D for drainage layout & design

Kirkton of Tealing

Tealing Church

Path



SP Design

Craigmaud Croft, Tillyfourie, Inverurie,
Aberdeenshire, AB51 7BJ
Tel: 01818 66264
Email: 01818-270142

Client: MR G NICOL


Project: ALTERATIONS TO CHURCH TO
CREATE DWELLING HOUSE AT
KIRKTON OF TEALING, DUNDEE

Drawing Title: BLOCK PLAN

Client: GDP	Date: SEP 18	Scale: 1:200 @ A1
Job No: 19-010	Drawing No: 08	Rev: F

This drawing is the property of SP Design and must not be reproduced or distributed without prior written authorisation from SP Design.







NORTH ELEVATION



WEST ELEVATION



SOUTH ELEVATION



EAST ELEVATION



SP Design

Craigmaud Croft, Tillyfourie, Inverurie,
Aberdeenshire, AB51 7SU
Tel: 01776 564616
Mob: 07796 270142

Client:

MR G NICOL

Project:

ALTERATIONS TO CHURCH TO
CREATE DWELLING HOUSE AT
KIRKTON OF TEALING, DUNDEE

Drawn by:

ELEVATIONS

Scale:

SOP

Date:

SEP 18

Sheet:

1:100 @ A1

Job No:

19-010

Drawing No:

07

Rev:

C

This drawing is the property of SP Design and must not be reproduced or distributed without prior written authorisation from SP Design.









GROUND FLOOR FROM GALLERY




MEMORIALS 1 & 2



MEMORIAL 3



MEMORIAL 4



MEMORIAL 5





GROUND FLOOR



FIRST FLOOR ROTTEN



PULPIT



MEMORIAL 6



MEMORIAL 7

SP Design
 Craigmaud Croft, Tillyfourie, Inverurie,
 Aberdeenshire, AB51 7SU
 Tel: 01453 68456
 Mob: 07760 27042


MR G NICOL

**ALTERATIONS TO CHURCH TO
 CREATE DWELLING HOUSE AT
 KIRKTON OF TEALING, DUNDEE**

SURVEY DRAWING - GROUND FLOOR

SDP	JUL 19	T 80 @ A1
19-010	10	A

This drawing is the property of SP Design and shall remain the property of SP Design. It shall not be used for any other purpose without the written consent of SP Design.



PROPOSED GROUND FLOOR PLAN

General Notes
 All dimensions in millimetres unless otherwise stated. Contractor to check all dimensions on site prior to commencement of work and any discrepancies to be notified to the Clerk of Works. All work to be carried out in accordance with the current Building Regulations and Code of Practice. All workmanship on site to be carried out in accordance with BS 8002. All alterations and new structural elements shall be in accordance with BS 5951. All structural steelwork shall be in accordance with BS 5951. All steelwork shall be in accordance with BS 5951. All steelwork shall be in accordance with BS 5951.

Foundations
 Where part foundations to be Grade C25, at a minimum depth of 450mm below existing Floor level. 50mm mass filling concrete Grade C75 to be laid under all part foundations unless Foundation concrete is placed immediately after excavation. Where the necessary excavation has been made a suitable working surface is to be laid and a minimum of 100mm concrete shall be laid over this concrete. Any steel passing through exterior walls to be finished over or embedded in concrete.

DPC
 150mm vertical D.P.C. to all openings & 225mm horizontal D.P.C. to horizontal thresholds.

Ground Floor
 Existing floor areas to be removed and floor to be replaced in accordance with the principles set out in BS754 (Insulation) Approved Code of Practice (Volume 2) 2010. In addition, the new construction within Building Regulations (Approved Document) Part D 2010 Thermal insulation, existing floor 2010 within should be followed.

Listing Thermal Bridging and Air Infiltration
 Building elements to be designed and constructed in accordance with the principles set out in BS754 (Insulation) Approved Code of Practice (Volume 2) 2010. In addition, the new construction within Building Regulations (Approved Document) Part D 2010 Thermal insulation, existing floor 2010 within should be followed.

Air Infiltration
 Airtightness of air in building to be prevented as far as necessary provided by:
 a. sealing by fitting joints between walls, ceilings and floors and at windows, doors and roof openings.
 b. sealing repair control membranes in timber framed and other framed panel construction.
 c. sealing of service pipe penetrations through the fabric of the building and around pipe and other service loading.
 d. fitting of draft exclusion strips in the frames of opening windows, external doors and rooflights.

Roof
 North facing roof to be stripped back and replaced with new 225mm thick timber reinforced working boards with 20mm gaps between for ventilation of the roof space. Proctor finished to receive existing felt and apply underlayment from existing roof. South facing roof shall be removed apart from existing boards to be replaced as required. Underlayment and battings to be retained as required with 20mm gaps between battings to be replaced/repaired as required as noted on the roof plan.

Fire Detection System
 Smoke and heat alarm shall be an independent circuit at the main distribution board and to have battery backup, installed in accordance with Part 9 of the Building Regulations and to comply with BS 5839 Part 6: 2004. System to comprise of at least 1 smoke alarm in every circulation space such as hallway and landing, and at least 1 heat alarm installed in every bedroom. Every room and adjoining access route on a landing at a height of not more than 2.2m should be provided with an additional smoke alarm to give the occupants early warning. Where the access route is a kitchen, the type of detector should be carefully considered to reduce the likelihood of false alarm. Detailed guidance on the detection and low alarm systems is available on the BS 5839 Part 6: 2004. All work to comply with part 9 of the Building Regulations.

Electrical
 All electrical work to be in accordance with the current BS regulations and to the satisfaction of the local authority. Contractor to supply and install MCB or equal approved consumer unit sized to meet the load and comply with BS 7671: 2001 and part 4.1 of the Building Regulations. Cables and conductors shall be installed in accordance with BS 7671: 2001 and part 4.1 of the Building Regulations. Cables and conductors shall be installed in accordance with BS 7671: 2001 and part 4.1 of the Building Regulations. Cables and conductors shall be installed in accordance with BS 7671: 2001 and part 4.1 of the Building Regulations. Cables and conductors shall be installed in accordance with BS 7671: 2001 and part 4.1 of the Building Regulations.



SP Design
 Craigmaud Croft, Tillyfourie, Inverurie,
 Aberdeenshire, AB51 7S.J
 Tel: 01573 564700
 Mail: 0156 270442


MR G NICOL

**ALTERATIONS TO CHURCH TO
 CREATE DWELLING HOUSE AT
 KIRKTON OF TEALING, DUNDEE**

Drawing No:
GROUND FLOOR PLAN

Rev	SDP	SEP 18	1:50	A1
1	15-010	02		C

This drawing is the property of SP Design and shall not be reproduced or used in any way without the written consent of SP Design.




PROPOSED FIRST FLOOR PLAN

External Walls
Existing joints in external walls to be patched and reinforced with suitable mortar in accordance with the painting department. All window frames to be left unobstructed and repaired. Finishing work to be checked on completion of renovation works.

Internal Walls
All existing internal wall cracks to be left unobstructed and repaired.
New Partitions
New timber partitions to be constructed in 150 x 40mm C17 treated timber, double top and bottom rails with 10mm gaps, and wall studs with 12.5mm thick panel bonded tapered edge plasterboard with joints taped and fixed. Any new partition or external wall to be clad with 12.5mm thick full face tapered edge plasterboard. All new partitions to be fixed with 150mm thick Rockwool quilt insulation.

Manual Controls
The location of a manual control device can have a significant effect on both the ease of operation of the device and safety in use. Features that are inaccessible present a greater risk of accident when handling or resetting. Any controls that are intended for operation by the occupants of a building should be located in a position that allows safe and convenient use. This guidance is applicable to manual controls to operate mechanical, including windows and rooflights and to controls and outlets of electrical fixtures located on a wall or other vertical surface. Controls incorporating a window or other protective device for safety reasons, controls should be operated with one hand.

An operable window, rooflight or other ventilation that provides natural ventilation to meet Standard 3.14, should have controls for opening, positioned at least 850mm from any internal corner, projecting wall or window obstruction and at a height of:
- not more than 1.7m above floor level, where access to controls is unobstructed or
- not more than 1.2m above floor level, where access to controls is hindered by a fixed obstruction, and more than 850mm high where projects not more than 850mm in front of the position of the controls, such as a kitchen base unit. Where obstruction is greater, a vertical means of opening, in an unobstructed location, should be provided.
- not more than 1.2m above floor level, in an unobstructed location, with an enhanced specified open area 0.11 m² or within accessible secondary accommodation (see clause 3.12.2) not provided with mechanical ventilation.
The above guidance does not apply to windows or rooflights operated only for cleaning or maintenance purposes or that are controlled by an automatic system, or to double windows, double doors, controls and controls of mechanical fixtures and systems should be positioned at least 850mm from any internal corner, projecting wall or window obstruction and, unless the need for a higher location can be demonstrated, not more than 1.2m above floor level. This would include fixtures such as sockets, switches, the earth call points and other controls or programming, within the height range.
- light switches should be positioned at a height of between 850mm and 1.7m above floor level.
- standard switched or unswitched socket outlets and outlets for other services such as telephone or television should be positioned at least 850mm above floor level. Above an obstruction, such as a window, fixture should be at least 150mm above the projecting surface. Where sockets are connected, such as to the rear of white goods in a kitchen, separate switching should be provided in an accessible position, to allow appliances to be switched.



SP Design
Craigmaud Croft, Tillyfourie, Inverurie,
Aberdeenshire, AB51 7SU
Tel: 01473 582656
01607796 270162

Client: **MR G NICOL**

Project: **ALTERATIONS TO CHURCH TO CREATE DWELLING HOUSE AT KIRKTON OF TEALING, DUNDEE**

Drawn by: **FIRST FLOOR PLAN**

SDP	SEP 18	1:50 @ A1	
19-010	03	B	

This drawing is the property of SP Design and shall remain the property of SP Design. All other rights reserved.
Information not for design.

